

EC-Safety Data Sheet conforming to 1907/2006/EG, Article 31

Ciric LM 3 K

Date 31.07.2019 Page 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	Ciric LM 3 K
1.2 Relevant identified uses of the substance or mixture and uses advised against	Lubrication Paste - Only suitable for industrial use. Not suitable for commercial or private use.
1.3 Details of the supplier of the safety data sheet	MOLYDUVAL GmbH * Halskestr.6 * 40880 Ratingen * Germany * +49 (2102) 9757-00 * safety@molyduval.com
1.4 Emergency telephone number	+49 (2102) 9757-20 (24h)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture 1272/2008/EG	hazard statements / category of danger / Hazard class H412 / Aquatic Chronic 3 / Harmful to aquatic life with long lasting effects. The product is classified acc to 1272/2008/EG
2.2 label elements	H412 Harmful to aquatic life with long lasting effects. P273 Avoid release to the environment. P501 Dispose of contents and container in accordance with local regulations of the disposal.
2.3 Other hazards	-

SECTION 3: Composition - Information on Ingredients

3.2 Mixtures	Mixture of substances listed below with nonhazardous additions. ----- 2,5 % - 25,0 % Copper powder EG: 231-159-6 CAS: 7440-50-8 Reach: 01-2119480154-42 H302 Acute Tox. 4 / H400 Aqua Acute 1 / H411 Aqua Chron. 2 (MFCICU)
--------------	--

SECTION 4: First Aid Measures

General Instructions	Remove victim from danger zone, without exposing yourself to any personal risk. Remove wetted clothing and shoes and clean items before using them again.
After Inhalation	Remove exposed person to fresh air.
After Skin Contact	Wash with plenty of soap and plenty of water. Consult a doctor if skin irritation persists.
After Eye Contact	Long lasting rinse Rinse opened with water, if necessary, use eye wash. If symptoms persist, seek medical advice.
After Ingestion	Rinse mouth and drink plenty of water. Do not induce vomiting. If symptoms persist, seek medical advice.
Most important symptoms and effects, both acute and delayed	No information available
Indication of any immediate medical attention and special treatment needed	Prolonged or repeated exposure may cause skin discomfort.

SECTION 5: Fire-Fighting Measures

5.1 Extinguishing media	Suitable extinguishing media : Water spray. Foam. Dry powder. Carbon dioxide (CO2). Unsuitable extinguishing media : Strong water jet.
5.2 Special hazards arising from the substance or mixture	In case of a fire, there may arise poisonous (CO, CO2 and other organic gases) gases. Run-off does not allow to enter drains or watercourses by firefighters.
5.3 Advice for firefighters	If necessary, use in case of fire, self contained breathing apparatus. Collect contaminated firefighting water separately, must not be discharged into drains. Fire residues and contaminated firefighting water must be disposed of in accordance with local regulations. Extinguishing measures to the surroundings. Standard procedure for chemical fires. Extinguishing measures to the surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	Wear personal protective equipment. Avoid contact with eyes and skin.
6.2 Special Environmental Protection	Avoid entering into drains, water courses or soil. Fire or police agree, if the product has escaped into a water course or sewage system, or has contaminated the soil and plants.
6.3 Methods and material for containment and cleaning up	Use oil sucking materials f.e chemical absorbents.

EC-Safety Data Sheet conforming to 1907/2006/EG, Article 31

Ciric LM 3 K

Date 31.07.2019 Page 2

6.4 Reference to other sections n.a.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling Advice on safe handling: Do not breathe mixture. Avoid generation of vapors and aerosols. Hygiene measures: Immediately change contaminated clothing. Preventive skin protection. Wash hands and face after work.

7.2 Conditions for safe storage, including any incompatibilities Store in closed containers. Open container in well ventilated areas
Storage Class VCI: 11 Flammable Solids

SECTION 8: Limiting and supervising the exposure / personal protection

8.1 Control parameters Copper powder EG: 231-159-6 CAS: 7440-50-8 Reach: 01-2119480154-42:
Kupfer CAS 7440-50-8
Inhaltsstoffe CAS-Nr. Werttyp (Art der Exposition) Zu überwachende Parameter Stand
Grundlage
AGW (Alveolengängige Fraktion) 1 mg/m³ 2009-02-16 DE TRGS 900
Weitere Information Ausschuss für Gefahrstoffe
DNEL: Kupfer (7440-50-8) Anwendungsbereich: Arbeitnehmer Expositionswege:
Hautkontakt Mögliche Gesundheitsschäden: Kurzzeit - systemische Wirkungen Wert: 273 mg/kg
DNEL: Kupfer (7440-50-8) Anwendungsbereich: Arbeitnehmer Expositionswege: Einatmen
Mögliche Gesundheitsschäden: Kurzzeit - systemische Wirkungen Wert: 20 mg/m³
DNEL: Kupfer (7440-50-8) Anwendungsbereich: Arbeitnehmer Expositionswege:
Hautkontakt Mögliche Gesundheitsschäden: Langzeit - systemische Wirkungen Wert: 137 mg/kg
DNEL: Kupfer (7440-50-8) Anwendungsbereich: Verbraucher Expositionswege: Hautkontakt
Mögliche Gesundheitsschäden: Kurzzeit - systemische Wirkungen Wert: 273 mg/kg
DNEL: Kupfer (7440-50-8) Anwendungsbereich: Verbraucher Expositionswege: Einatmen
Mögliche Gesundheitsschäden: Kurzzeit - systemische Wirkungen Wert: 20 mg/m³
PNEC: Kupfer (7440-50-8) Boden Wert: 65,5 mg/kg
PNEC: Kupfer (7440-50-8) Süßwasser Wert: 0,0078 mg/l
PNEC: Kupfer (7440-50-8) Süßwassersediment Wert: 87 mg/kg
PNEC: Kupfer (7440-50-8) Meerwasser Wert: 0,0052 mg/l
PNEC: Kupfer (7440-50-8) Meeressediment Wert: 676 mg/kg
PNEC: Kupfer (7440-50-8) STP Wert: 0,230 mg/l

8.2 Limitation and supervision of exposure - Personal Protective Equipment Respiratory protection: Not required, except in case of aerosol formation. Avoid inhalation of vapors. Use respiratory protective device against the effects of fumes / dust / aerosol. Combination filter, eg. As DIN 3181 ABEK
Hand protection: Gloves - oil resistant. Glove material: nitrile rubber, butyl rubber or fluoro rubber. Recommended thickness: = 0,4 mm. Penetration time of glove material Value for the permeation: Level = 480 min. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of breakthrough time is recommended.
Eye protection: Safety glasses
Hygiene measures: Wash hands before breaks and immediately after handling the product. Keep working clothes separately. Take off all contaminated clothing immediately.
Protective measures: Handle in accordance with good industrial hygiene and safety practice.
Body protection: work clothes

8.3 Delimitation and monitoring of environmental exposure Do not discharge into surface water or drains

SECTION 9: Physical and Chemical Properties

Appearance Form	pasty
Color	copper
Appearance	like grease
Odour	without
Boiling Point / Boiling Range	-
Melting Point / Melting Range	-
Flash Point	Not applicable
Autogenous Ignition Temperature	-
Upper Explosion Limit	-

EC-Safety Data Sheet conforming to 1907/2006/EG, Article 31

Ciric LM 3 K

Date 31.07.2019 Page 3

Lower Explosion Limit	-
Vapor Density	-
Specific Gravity, 20°C	0,91 g/cm ³
Water Solubility	No
Partition Coefficient n-oct/water	-
VOC-Content	-

SECTION 10: Stability and Reactivity

10.1 Reactivity	This product is stable in normal-use temperatures.
10.2 Chemical Stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Fumes can combine with air to form an explosive mixture.
10.4 Conditions to be avoided	No information available
10.5 Incompatible Materials	no information available
10.6 Hazardous products of instability / decomposition	no

SECTION 11: Toxicological Information

Toxicological Information	Copper powder EG: 231-159-6 CAS: 7440-50-8 Reach: 01-2119480154-42: Schätzwert Akuter Toxizität : 571,82 mg/kg
Symptoms after ingestion	Provoking the mucous membranes with high concentrations.
At Skin Contact	Causes skin irritation. Causes serious eye damage.
Symptoms after Inhalation	Irritation of mucous membranes
Symptoms after eye contact	Risk of serious damage to eyes
Other information	No sensitizing effects known.
Toxicological Tests	There are no human toxicological data.
Further Toxicologic Effects	The product is classified acc to 1272/2008 [CLP]

SECTION 12: Ecological Information

12.1 Toxicity	Copper powder EG: 231-159-6 CAS: 7440-50-8 Reach: 01-2119480154-42: Kupfer (7440-50-8) : M-Faktor : 10
12.2 Persistence and degradability	Ecotoxicological data have not been determined specifically for this product. The information provided is based on the knowledge of the components. Product is not readily biodegradable. The main constituents are expected to be inherently biodegradable, but some components that may persist in the environment.
12.3 Bioaccumulative potential	not information available
12.4 Mobility in soil	No information available
12.5 Results of PBT and vPvB assessment	No information available
12.6 Other adverse effects	No information available

SECTION 13: Disposal Considerations

13.1 Waste treatment methods	May not be disposed together with domestic rubbish. Disposal in compliance with federal, state, and local laws. EÄK Waste Product Code : 130899 Olabfälle, nicht anders spezifiziert
------------------------------	--

SECTION 14: Transport information in accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN-No	Not classified as dangerous in the meaning of transport regulations
14.2 UN proper shipping name	No
14.3 Transport hazard class	No transport regulations.
14.4 Packing group	-
14.5 Environmental hazards	n.a.

EC-Safety Data Sheet conforming to 1907/2006/EG, Article 31

Ciric LM 3 K

Date 31.07.2019 Page 4

14.6 Special precautions for user No information available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture DE: water polluting category: 2
DE: Employment restrictions concerning juveniles must be observed (§ 22 JArbSchG).

15.2 Chemical safety assessment There is no information available

SECTION 16: Further Information

16.1 Full text of the dangers in section 2 and 3 H412 Harmful to aquatic life with long lasting effects.
P273 Avoid release to the environment.
P501 Dispose of contents and container in accordance with local regulations of the disposal.

16.2 Further Information The information in this SDS is correct to the best of our knowledge at the time of its publication. The information is intended to give you advice about the safe handling of the product named in this safety during storage, processing, transport and disposal. The details are not transferable to other products. The information given in this safety combination with any other materials or in any process, or undergoes processing, can use the information in this SDS, to the extent that it does not specifically indicate otherwise, are not transferred to the new made material. The material data referred to in item 9 are safety information, but no guarantees on properties. Warranties are excluded without clarification of the technical intended use and the operating conditions. If you have further questions we are available.