

MOLYDUVAL

Ciric AKM 2 K



Special Paste for Socket Tools

Copper coloured, solid lubricant paste based on mineral oil thickened with aluminium complex soap. The product is developed as a lubrication agent for chisels.

Properties

- * good anticorrosive properties
- * free of sulfure
- * free of lead and nickel
- * good water resistance
- * good separating properties
- * good sealing properties
- * good heat deduction
- * good tackiness

Applications

* in air-hoses or micro-fog lubricators for lubrication of hammers, chisels, pile-drivers, drills, grinders, pumps, hoists, clamps and vices

Technical Datas

Color		copper
Consistency Class NLGI		2
Name		MPF2U-30
Base Fluid		Mineral
Thickener		AlK
Density 15°C	kg/m ³	1000
Viscosity Base Fluid, 40°C	mm ² /s	300
Temperature Range	°C	-30 -> +1200
Water Resistance	Bewertungs	0-90

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.