

MOLYDUVAL

Grundo MP 15



Base Fluid for Lubricant Manufacturing

A paraffinic base fluid for use in a wide variety of applications.

Properties

- * good anticorrosive properties
- * oxidation resistant
- * high viscosity index
- * relative low residue forming
- * high flash point
- * low foam forming
- * good demulsifying properties

Applications

- * for circulation systems
- * as separating agent for moulds
- * for vacuum pumps, mechanical and diffusions pumps
- * for stamping and forming precious metals, copper, brass, etc.
- * as separating agent for moulds in glass industry
- * as parting agents when pressing, syringe, vacuum-forms, e.g. during the elastomer production and in the plastic processing industry

Technical Datas

Viscosity Class	ISO-VG	15
Density 20°C	kg/m ³	850
Color		0,5
Pour Point	°C	-12
Viscosity 40°C	mm ² /s	15
Flash Point	°C	194
Viscosity Index		99

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.