

# MOLYDUVAL

## Grundo MP 460



### Mineral base oil for the production of lubricants

Paraffinic based solvent neutral oil with high viscosity index.

#### Properties

- \* good anticorrosive properties
- \* oxidation resistant
- \* good foam behaviour
- \* relative low residue forming
- \* good oil/water separation properties, easy drainage of excess water from lubrication systems
- \* high flash point
- \* low foam forming
- \*

#### Applications

- \* for manufacturing of lubricants
- \* for manufacturing of release agents
- \* for producing chemical technical products

#### Technical Datas

Density 20°C	kg/m <sup>3</sup>	890
Pour point	°C	-12
Viscosity 40°C	mm <sup>2</sup> /s	460
Flash Point	°C	290

For further information, please see our website [www.molyduval.com](http://www.molyduval.com) or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.