

MOLYDUVAL

Moralub FB 100 Z



Brass Pressing Lubricant

Semisynthetic fluid for operations of heavy duty brass forging, suitable for high production rates and noticeable material sliding inside of die cavity. Used in applications where perfect coating and protection of punches are required.

Properties

- * good moistening
- * contains solid lubricants
- * semi synthetic

Applications

- * for tool and workpiece lubrication in hot metal forming like forging or moulding
- * for forging of fittings and valves etc, including brass continuous and semi-continuous casting operations

How to Use

Is generally used undiluted. The application should be done with a spray gun or an automatic spray system.

Technical Datas

Color		white
Base Fluid		Min + Syn
Density 15°C	kg/m ³	910
Viscosity Base Fluid, 40°C	mm ² /s	120

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.