

MOLYDUVAL

Nora UA 2



Low-Noise Rolling Bearing Grease

Synthetic multi purpose lubricating grease with a particularly low noise level. For ball bearings with economical long-term or lifetime lubrication.

Properties

- * high pressure ability
- * very good corrosion protection
- * good walking resistance
- * very good tackiness
- * low friction coefficient
- * good resistant against cold and hot water, even sea water

Applications

- * for bearings in high temperature sectors, ventilators, ovens, motors
- * for anti-friction bearings in small motors
- * for bearings in precision engineering, for for-life-lubrication
- * for anti-friction and sleeve bearings in textile industry
- * for sintered metal plain bearings in household, pumps, blowers
- * for rolling and sleeve bearings
- * for anti-friction bearings in small motors

Technical Datas

| | | |
|--|--------------------|--------------|
| Color | | blue |
| Consistency Class NLGI | | 2 |
| Name | | KP2R-50 |
| Base Fluid | | PAO |
| Name | | ISO-L-XEFEB2 |
| Density 15°C | kg/m ³ | 880 |
| Viscosity Base Fluid, 40°C | mm ² /s | 100 |
| Water Resistance Static | Grade | 0-90 |
| Temperature Range | °C | -50 -> +180 |
| Temperature Range shortly up to | °C | 220 |
| nd value n-d | | 700.000 |
| Dropping Point | °C | > 250 |
| Corrosion Protection Emcor, WWO, distilled water | Grade | 0 |

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

The indicated speed factors are guide values which depend on the type and diameter of the bearing and the local operating conditions, which is why they have to be confirmed in tests carried out by the user in each individual case.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.